



The thinnest mounting profile available.

APPLICATIONS

The THINLINE™ Hose Reel is a general purpose 2-port reel that offers the thinnest mounting profile available on the market. The reel design enhances driver visibility and protects the reel from damage. THINLINE Hose Reels may be used for both new and replacement installations on most two, three or four stage masts.

FEATURES

Narrow Profile



- Achieved through a unique design in combination with SAE 100-R7 thermoplastic twin bonded hose.
- A general purpose weld-on mounting bracket is used for most masts allowing a narrow mounting profile to be achieved from a number of different mounting positions.
- Mounting bracket provides the flexibility to compensate for interference from lift cylinders, tilt anchors, overhead guards and crossmembers.
- Simplicity of design and construction make the THINLINE Hose Reel exceptionally easy to service.

OPTIONS

- Twinline Bonded Hose
- Mounting Brackets—All Masts
- Hose Terminal—Down
- Hose Terminal—Up Connection
- Fitting Group



Narrow mounting profile for better visibility & less damage.



Contents

- Thinline Reel
- Hose Reel Hose
- Hose Terminal–Down
- Fittings


Hose Reel

Group Package

Mounting Location	Catalog Order No.	Mounting Location	Catalog Order No.	Hose Size	Flange Size	Total Hose Length	Usable Hose Length	Weight (Lbs.)
Hose Reel								
Right Hand	672570	Left Hand	672571	#4 ①	11"	154"	136"	20
Right Hand	672572	Left Hand	672573	#6 ①	13"	180"	152"	28
Right Hand	672574	Left Hand	672575	#6 ①	16"	300"	272"	32
Right Hand	672576	Left Hand	672577	#8 ①	16"	228"	194"	38
Group Package								
Right Hand	673560	Left Hand	673561	#4	11"	154"	136"	25
Right Hand	673562	Left Hand	673563	#6	13"	180"	152"	34
Right Hand	673564	Left Hand	673565	#6	16"	300"	272"	41
Right Hand	673566	Left Hand	673567	#8	16"	228"	194"	47

① Hose not included.

► Thinline Hose Reel Group Packages are a practical and economical choice for both new and replacement installations. Replacing existing reels with a Thinline Group Package will allow you to achieve the Thinline Reel's extremely narrow mounting profile.



Contents

- Thinline Hose Reel(s)
- Hose Reel Hose
- Header Hoses ②
- Hose Terminals–Down
- Hose Terminals–Up
- Fittings
- Mounting Brackets for Hose Reel and Hose Terminals (Weld-On)

Hose Reel Hydraulic Supply Groups

	Mounting Location	Catalog Order No.	Mounting Location	Catalog Order No.	Hose Size	Maximum Mast Down Height ①	Reel Diameter	Attachment Functions	Package Weight (Lbs.)
2 Stage Masts	Right Hand	673592	Left Hand	223027	#4③	120"	11"	RH/1 LH/2	35
	Right Hand	673594	Left Hand	674516	#6	120"	13"	1	46
	Right Hand	673598	Left Hand	685263	#8	120"	16"	RH/1 LH/2	62
3 Stage Masts	Right Hand	673592	Left Hand	223027	#4③	83"	11"	RH/1 LH/2	46
	Right Hand	673594	Left Hand	674516	#6	95"	13"	1	46
	Right Hand	673596	Left Hand	206687	#6	152"	16"	1	53
	Right Hand	673598	Left Hand	685263	#8	127"	16"	RH/1 LH/2	62
4 Stage Masts	Right Hand	673594	Left Hand	674516	#6	71"	13"	1	46
	Right Hand	673596	Left Hand	206687	#6	107"	16"	1	53
	Right Hand	673598	Left Hand	685263	#8	83"	16"	1	62

① For down heights greater than shown, contact Cascade. Normally the reel is mounted on upper top part of mast channel. If mounted elsewhere, check usable hose length.

② Header hoses may require shortening for best fit. Additional fittings may be required for auxiliary valve connection.

③ Hose Terminal–Up connection not included.

► Thinline Hose Reel Hydraulic Supply Groups contain all necessary components to plumb from the auxiliary valve bulkhead to the mast carriage.

► Separately priced Installation Kit is needed to complete normal hydraulic system installation. One or two required depending upon hydraulic functions.